



FEATURES

- Ø50 Radio tubular motor mono directional 433,42MHz**
- **Technology:** Radio mono directional 433,42MHz
 - **Motor Head:** Star
 - **Nr of end limits:** 2 + intermediate position
 - **Adjustment type:** Electronic
 - **End limits setting tool:** remote control
 - **Basic crown for tube Ø:**
 - **Nominal voltage:** 230V~ / 50Hz
 - **Thermal time:** 4 minutes in accordance with EN 60335-2-97
 - **Obstacle detection:** NO
 - **Freeze detection:** YES
 - **System of protection:** IP 44
 - **Insulation class:** I
 - **Temperature working range:** - 20°C to + 70°C
 - **Activation:** by remote control 433,42MHz
 - **Parallel connection:** YES
 - **Radio compatibility:** YES with controls 433,42 MHz
 - **Transmission frequency:** 433,42MHz
 - **Coding:** Rolling code 16 million of possibilities
 - **Memory capacity:** 12 remote controls - 1 sensor
 - **Range:** 20 m with 2 reinforced concrete walls to be passed through
 - **Made in:** Italy
 - **Certifications:** CE - CMIM - NF - VDE



COMPLIANCE

- EN 62233
- EN 60 335-2-97
- EN 301 489-3 V1.6.1:2013
- EN 301 489-1 V1.9.2:2011
- EN 300220-1 V3.1.1:2017
- EN 300220-2 V3.1.1:2017
- EN 55014-2:2015
- EN 55014-1:2006 + A1:2009 + A2:2011


HEAD AESTHETICS

- Plastic cap color:**
GREY
- Logo on the cap:**
NO



CABLE TYPE:

- Unpluggable
- H05 VVF 3 x 0,75 L. 3 m - White



TUBE AESTHETICS

- Tube color:**
RAL 5010 Gentian Blue
FE360 UNI EN 10305-3-2010



- CABLE CONNECTOR**
NO

**NOT INCLUDED
IN THIS CONFIGURATION**

DIMENSIONS



TECHNICAL DATA

REFERENCE	CUSTOMER REFERENCE	DESIGNATION	NOMINAL TORQUE	NOMINAL SPEED	NOISE LEVEL	RATED POWER	RATED CURRENT	CAPACITY OF THE LSU	LENGTH	MOTOR WEIGHT	FORECAST ANNUAL VOLUMES
9800412	/	AZ D50 R 6/17	6 Nm	17 Rpm	47 dBA	100 W	0,43 A	infinite	576 mm	2,14 Kg	700
9800413	/	AZ D50 R 10/17	10 Nm	17 Rpm	47 dBA	120 W	0,52 A	infinite	576 mm	1,95 Kg	1000
9800414	/	AZ D50 R 20/17	20 Nm	17 Rpm	53 dBA	190 W	0,83 A	infinite	596 mm	2,09 Kg	500
9800415	/	AZ D50 R 30/17	30 Nm	17 Rpm	55 dBA	240 W	1,04 A	infinite	631 mm	2,22 Kg	300
9800416	/	AZ D50 R 40/17	40 Nm	17 Rpm	57 dBA	240 W	1,04 A	infinite	631 mm	2,22 Kg	300
9800417	/	AZ D50 R 50/12	50 Nm	12 Rpm	55 dBA	240 W	1,04 A	infinite	631 mm	2,22 Kg	200