



FEATURES

- Ø60 Radio tubular motor mono directional 433,42MHz**
- **Technology:** Radio mono directional 433,42MHz
 - **Motor Head:** Round
 - **Nr of end limits:** 2 + intermediate position
 - **Adjustment type:** Electronic
 - **End limits setting tool:** remote control
 - **Basic crown for tube Ø:**
 - **Nominal voltage:** 230V~ / 50Hz
 - **Thermal time:** 4 minutes in accordance with EN 60335-2-97
 - **Obstacle detection:** NO
 - **Freeze detection:** YES
 - **System of protection:** IP 44
 - **Insulation class:** I
 - **Temperature working range:** - 20°C to + 70°C
 - **Activation:** by remote control 433,42MHz
 - **Parallel connection:** YES
 - **Radio compatibility:** YES with controls 433,42MHz
 - **Transmission frequency:** 433,42MHz
 - **Coding:** Rolling code 16 million of possibilities
 - **Memory capacity:** 12 remote controls - 1 sensor
 - **Range:** 20 m with 2 reinforced concrete walls to be passed through
 - **Made in:** Poland
 - **Certifications:** CE - CMIM - NF - VDE



COMPLIANCE
EN 62233
EN 60 335-2-97
EN 301 489-3 V1.6.1:2013
EN 301 489-1 V1.9.2:2011
EN 300220-1 V3.1.1:2017
EN 300220-2 V3.1.1:2017
EN 55014-2:2015
EN 55014-1:2006 + A1:2009 + A2:2011

HEAD AESTHETICS


Plastic cap color:
GREY

Logo on the cap:
NO



CABLE TYPE:
Unpluggable

H05 VVF 3 x 0,75 L. 3 m - White



TUBE AESTHETICS

Tube color:
RAL 5010 Gentian Blue
FE360 UNI EN 10305-3-2010



CABLE CONNECTOR
NO

**NOT INCLUDED
IN THIS CONFIGURATION**

DIMENSIONS



TECHNICAL DATA

REFERENCE	CUSTOMER REFERENCE	DESIGNATION	NOMINAL TORQUE	NOMINAL SPEED	NOISE LEVEL	RATED POWER	RATED CURRENT	CAPACITY OF THE LSU	LENGTH	MOTOR WEIGHT	FORECAST ANNUAL VOLUMES
9800420	/	AZ D60 R 80/12	80 Nm	12 Rpm	66 dBA	290 W	1,26 A	infinite	695 mm	4,55 Kg	300
9800421	/	AZ D60 R 120/12	120 Nm	12 Rpm	65 dBA	400 W	1,74 A	infinite	695 mm	4,80 Kg	300